

Piaba West Drilling - 2017 - July 25 Press Release

Hole ID	From (m)	To (m)	Length (m)	Au (g/t)	Cut-off (g/t Au)	Target	Section	Length (m)	Dip	Azimuth
BRAZD534	35.00	36.00	1.00	0.37	0.3	Piaba Infill	1650W	111.05	-67	168
and	45.00	47.23	2.23	1.12	0.3					
and	61.00	105.46	44.46	1.13	0.3					
incl	70.34	72.30	1.96	4.81	1.0					
BRAZD535	163.00	165.00	2.00	3.08	0.3	Piaba Infill	1700W	228.03	-73	168
and	188.00	209.80	21.80	0.95	0.3					
BRAZD536	192.80	194.65	1.85	1.40	0.3	Piaba West	1800W	285.07	-73	168
and	205.00	206.00	1.00	0.57	0.3					
and	210.34	219.00	8.66	5.70	1.0					
incl	215.60	218.00	2.40	15.84	5.0					
and	230.00	251.00	21.00	1.29	0.3					
and	254.00	255.00	1.00	0.58	0.3					
and	258.00	269.00	11.00	0.96	0.3					
BRAZD537	88.50	90.00	1.50	0.54	0.3	Piaba West	1850W	200.70	-63	168
and	102.00	109.00	7.00	1.22	0.3					
and	125.00	146.20	21.20	0.59	0.3					
and	152.20	157.00	4.80	0.87	0.3					
and	173.00	176.00	3.00	0.36	0.3					
BRAZD538	116.50	118.50	2.00	0.80	0.3	Piaba West	1850W	236.93	-71	168
and	128.50	133.60	5.10	2.29	0.3					
and	146.30	171.55	25.25	1.33	0.3					
and	179.30	182.80	3.50	1.16	0.3					
and	186.00	189.00	3.00	0.41	0.3					
BRAZD539	81.30	82.00	0.70	1.54	0.3	Piaba Infill	1750W	160.94	-64	168
and	88.85	90.30	1.45	1.96	0.3					
and	102.00	108.00	6.00	0.92	0.3					
and	111.35	144.00	32.65	1.07	0.3					
BRAZD540	109.00	112.00	3.00	1.25	0.3	Piaba Infill	1750W	176.85	-71	168
and	129.00	134.00	5.00	0.78	0.3					
and	139.10	147.00	8.00	3.63	0.3					
incl	141.00	147.10	6.10	4.56	1.0					
and	155.80	158.00	2.20	0.58	0.3					
and	169.20	170.00	0.80	1.61	0.3					
BRAZD541	82.00	83.00	1.00	2.23	0.3	Piaba Infill	1750W	205.30	-76	168
and	129.70	130.20	0.50	1.63	0.3					
and	136.00	138.00	2.00	0.89	0.3					
and	140.00	145.00	5.00	0.53	0.3					
and	152.60	159.00	6.40	1.50	0.3					
incl	152.60	153.60	1.00	5.81	5.0					
and	165.00	176.10	11.10	1.38	0.3					
and	190.00	191.00	1.00	0.78	0.3					
BRAZD542	130.00	142.20	12.20	3.20	0.3	Piaba West	2100W	176.65	-56	168
incl	130.00	137.00	7.00	4.32	1.0					
BRAZD543	14.00	17.00	3.00	0.63	0.3	Piaba West	1800W	110.10	-59	168
and	21.80	28.00	6.20	1.89	0.3					
and	30.70	35.50	4.80	0.67	0.3					
and	42.50	46.50	4.00	0.65	0.3					
and	90.00	94.00	4.00	2.60	0.3					
incl	92.00	94.00	2.00	4.84	1.0					

Hole ID	From (m)	To (m)	Length (m)	Au (g/t)	Cut-off (g/t Au)	Target	Section	Length (m)	Dip	Azimuth
BRAZP586	No significant results					Piaba West	2000W	49.00	-55	168
BRAZP589	No significant results					Piaba West	2300W	90.00	-55	168
BRAZP594	25.00	26.00	1.00	4.82	0.3	Piaba West	1850W	168.00	-60	168
and	98.00	110.00	12.00	0.71	0.3					
and	111.00	115.00	4.00	0.67	0.3					
and	122.00	123.00	1.00	0.76	0.3					
and	132.00	136.00	4.00	0.77	0.3					
BRAZP595	77.00	99.00	22.00	0.79	0.3	Piaba West	1800W	140.00	-70	168
and	102.00	117.00	15.00	1.43	0.3					
incl	102.00	109.00	7.00	2.17	1.0					
and	126.00	132.00	6.00	0.50	0.3					
BRAZP596	10.00	15.00	5.00	1.49	0.3	Piaba West	1800W	53.00	-59	168
and	19.00	39.00	20.00	5.06	0.3					
incl	19.00	21.00	2.00	28.67	1.0					
incl	24.00	38.00	14.00	2.92	1.0					
BRAZP597	No significant results					Piaba West	2050W	60.00	-55	168
BRAZP598	42.00	43.00	1.00	2.26	0.3	Piaba West	2050W	97.00	-55	168
and	58.00	66.00	8.00	0.48	0.3					
and	95.00	97.00	2.00	5.89	5.0					
BRAZP599	18.00	24.00	6.00	2.16	0.3	Piaba West	2100W	60.00	-55	168
BRAZP600	29.00	33.00	4.00	0.47	0.3	Piaba West	2100W	110.00	-55	168
and	102.00	106.00	4.00	0.46	0.3					
BRAZP601	No significant results					Piaba West	2150W	60.00	-55	168
BRAZP602	No significant results					Piaba West	2150W	90.00	-55	168
BRAZP603	39.00	47.00	8.00	0.45	0.3	Piaba Infill	1425W	100.00	-55	168
and	48.00	67.00	19.00	1.88	0.3					
incl	54.00	62.00	8.00	3.74	1.0					
and	72.00	79.00	7.00	0.48	0.3					
and	90.00	92.00	2.00	1.34	0.3					
BRAZP604	12.00	16.00	4.00	0.43	0.3	Piaba West	2000W	90.00	-50	168
and	32.00	42.00	10.00	0.89	0.3					
BRAZP605	39.00	40.00	1.00	0.75	0.3	Piaba West	1950W	90.00	-55	168
and	53.00	54.00	1.00	0.39	0.3					
and	60.00	65.00	5.00	0.40	0.3					
and	70.00	71.00	1.00	0.99	0.3					
BRAZP606	14.00	15.00	1.00	0.85	0.3	Piaba Infill	0300W	110.00	-65	168
and	32.00	34.00	2.00	0.93	0.3					
and	41.00	42.00	1.00	1.10	0.3					
and	58.00	61.00	3.00	1.06	0.3					
and	67.00	70.00	3.00	4.95	1.0					
and	80.00	84.00	4.00	3.32	1.0					
and	93.00	99.00	6.00	1.43	0.3					
and	104.00	108.00	4.00	1.31	0.3					
BRAZP607	7.00	9.00	2.00	2.84	0.3	Piaba Infill	1250W	70.00	-50	168
and	15.00	16.00	1.00	0.44	0.3					
and	20.00	37.00	17.00	1.26	0.3					
incl	23.00	31.00	8.00	1.95	1.0					
and	38.00	46.00	8.00	1.16	0.3					
and	48.00	52.00	4.00	0.76	0.3					
and	55.00	59.00	4.00	0.81	0.3					
BRAZP608	56.00	57.00	1.00	1.25	0.3	Piaba Infill	1500W	118.00	-63	168
and	73.00	81.00	8.00	0.80	0.3					
and	87.00	97.00	10.00	0.63	0.3					
BRAZP609	No significant results					Piaba West	2200W	90.00	-55	168

Hole ID	From (m)	To (m)	Length (m)	Au (g/t)	Cut-off (g/t Au)	Target	Section	Length (m)	Dip	Azimuth
BRAZP610	20.00	25.00	5.00	1.01	0.3	Piaba West	2150W	110.00	-55	168
and	28.00	34.00	6.00	2.13	0.3					
and	40.00	46.00	6.00	0.64	0.3					
and	52.00	53.00	1.00	0.38	0.3					
and	59.00	60.00	1.00	0.30	0.3					
BRAZP611	1.00	4.00	3.00	1.97	0.3	Piaba West	2050W	114.00	-56	168
and	96.00	97.00	1.00	0.49	0.3					
and	104.00	105.00	1.00	0.37	0.3					

#### **Qualified Person and Disclosure Statement**

Scott Heffernan, M.Sc., P.Geo., the Company's EVP Exploration and Qualified Person under National Instrument 43-101, has reviewed and verified that the technical information contained in this document is accurate and approves the written disclosure of the same. Drill composites were calculated using cut-off values of 0.3 g/t, 1.0 g/t or 5.0 g/t gold as specified in the drill table and contain no more than 3 metres of internal waste. Drill intersections are calculated using uncut assays and are reported as drilled thicknesses. True widths of the mineralized intervals are interpreted to be 60 to 90 percent of the reported lengths. All samples were submitted to ALS Chemex in Belo Horizonte, Brazil for sample preparation. Sample pulps were then sent to ALS Chemex in Lima, Peru for geochemical analysis for gold by fire assay of a 30-gram charge with an Atomic Absorption finish (AA) and for a 33 multi-element geochemical suite by 4-acid digestion and Inductively-Coupled Mass Spectrometry (ICP-MS). Samples with AA gold values over 10.0 g/t are re-assayed by Screen Metallics fire assay. Control samples (accredited standards, blanks and duplicate samples at the field and preparation stages) were inserted on a regular basis. Results were monitored upon receipt of assays.