

Genipapo Drilling - 2017

Hole ID	From (m)	To (m)	Length (m)	Au (g/t)	Cut-off (g/t Au)	Target	Section	Length (m)	Dip	Azimuth
BRAZD533	162.00	163.00	1.00	1.05	1.0	Genipapo		176.60	-55	45
BRAZD544	No significant results					Genipapo		206.80	-55	180
BRAZD545	50.00	52.00	2.00	1.08	0.3	Genipapo		220.25	-55	205
and	62.00	54.40	3.40	1.46	0.3					
and	68.00	72.60	4.60	1.24	0.3					
and	75.00	79.00	4.00	3.28	1.0					
and	82.00	84.00	2.00	0.75	0.3					
and	88.65	94.00	5.35	0.82	0.3					
and	101.00	101.85	0.85	5.54	0.3					
and	176.00	176.62	0.62	0.53	0.3					
and	178.00	179.00	1.00	0.34	0.3					
and	190.00	191.00	1.00	0.49	0.3					
BRAZD546	3.00	16.00	13.00	1.89	0.3	Genipapo		222.05	-55	0
incl	10.00	13.00	3.00	5.57	1.0					
and	29.00	32.68	3.68	0.95	0.3					
and	37.00	38.00	1.00	0.35	0.3					
and	42.00	45.70	3.70	1.61	0.3					
and	52.40	53.80	1.40	0.52	0.3					
and	59.00	60.00	1.00	0.47	0.3					
and	119.00	120.00	1.00	0.41	0.3					
and	145.70	147.45	1.75	0.46	0.3					
BRAZD547	37.00	38.00	1.00	1.53	1.0	Genipapo		183.49	-55	205
								1009.19		

Qualified Person and Disclosure Statement

Scott Heffernan, M.Sc., P.Geo., the Company's EVP Exploration and Qualified Person under National Instrument 43-101, has reviewed and verified that the technical information contained in this document is accurate and approves the written disclosure of the same. Drill composites were calculated using cut-off values of 0.3 g/t, 1.0 g/t or 5.0 g/t gold as specified in the drill table and contain no more than 3 metres of internal waste. Drill intersections are calculated using uncut assays and are reported as drilled thicknesses. True widths of the mineralized intervals are interpreted to be 60 to 90 percent of the reported lengths. All samples were submitted to ALS Chemex in Belo Horizonte, Brazil for sample preparation. Sample pulps were then sent to ALS Chemex in Lima, Peru for geochemical analysis for gold by fire assay of a 30-gram charge with an Atomic Absorption finish (AA) and for a 33 multi-element geochemical suite by 4-acid digestion and Inductively-Coupled Mass Spectrometry (ICP-MS). Samples with AA gold values over 10.0 g/t are re-assayed by Screen Metallics fire assay. Control samples (accredited standards, blanks and duplicate samples at the field and preparation stages) were inserted on a regular basis. Results were monitored upon receipt of assays.